

MANUFACTURE STANDARD, MANUFACTURE RELIANCE

RT-2600C

Microplate Washer



Features


- Easy Windows operation system, large LCD display
- Washes flat, U and V-bottom strips and plates
- 12-way or 8-way manifold, automatic and manual positioning
- Large memory, up to 50 wash protocols can be programmed
- Automatic monitoring for vacuum and pressure, automatic rinse cycle
- Washing pressure volume and time adjustable
- Liquid level detection and alert function
- No special airtight bottle required for wash bottle
- Easy maintenance

RT-2600C


Microplate Washer




Program interface





Select strip to wash



Manifold positioning



System setting



Technical Specifications

Plate Mode	96- or 48- well plate or strip
Dispense Precision	CV < 2%
Residual Volume	< 3 ul
Washing Volume	50-3000ul for 8-way manifold
	50-2000ul for 12-way manifold
Washing Cycle	Maximum 99 cycles
Strip Washing	1 to 12 channels adjustable
Soaking Time	0-24 hr
Display	5" LCD
Bottle Capacity	2 litres each
Memory	50 washing protocols
Interface	RS-232 serial port
Net Weight	9KG
Dimensions L×W×H (mm)	390×330×177
Power Supply	a.c. 100V-240V, 50Hz/60Hz

Rayto Life and Analytical Sciences Co.,Ltd.

2nd Floor, 5th Building, Software Park, NO.2, Gaoxinzhong
3rd Road, High-tech Industrial Park, Nanshan,
Shenzhen 518057, P.R. China
Tel: +86(755)86868996 Fax: +86(755)86168796
Email: info@rayto.com

